



US009409300B2

(12) **United States Patent**
Wong et al.

(10) **Patent No.:** **US 9,409,300 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **OPEN CUTTER FOR A FOIL TYPE SHAVER
AND METHOD FOR FABRICATING THE
OPEN CUTTER**

(2013.01); *B26B 19/04* (2013.01); *B26B 19/12*
(2013.01); *B26B 19/26* (2013.01)

(71) Applicant: **Raymond Industrial Limited**, Hong
Kong (HK)

(58) **Field of Classification Search**

CPC *B26B 19/044*; *B26B 19/384*; *B26B 19/04*;
B26B 19/12; *B26B 19/26*
See application file for complete search history.

(72) Inventors: **Ying Man John Wong**, Hong Kong
(HK); **Kwok Yung Anthony Law**, Hong
Kong (HK)

(56)

References Cited

U.S. PATENT DOCUMENTS

2,234,894 A * 3/1941 Bruecker *B26B 19/384*
30/346.51
7,022,195 B2 * 4/2006 Otani *B26B 19/044*
148/527

(73) Assignee: **RAYMOND INDUSTRIAL
LIMITED**, Shatin (HK)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

* cited by examiner

Primary Examiner — Sean Michalski

Assistant Examiner — Liang Dong

(74) *Attorney, Agent, or Firm* — Miller, Matthias & Hull
LLP

(21) Appl. No.: **14/860,679**

(22) Filed: **Sep. 21, 2015**

(65) **Prior Publication Data**

US 2016/0008993 A1 Jan. 14, 2016

Related U.S. Application Data

(62) Division of application No. 13/943,770, filed on Jul.
16, 2013, now Pat. No. 9,289,907.

(51) **Int. Cl.**

B26B 19/04 (2006.01)

B26B 19/38 (2006.01)

B26B 19/26 (2006.01)

B26B 19/12 (2006.01)

(52) **U.S. Cl.**

CPC *B26B 19/044* (2013.01); *B26B 19/384*

(57)

ABSTRACT

An open cutter for a foil type shaver includes a plurality of arch-shaped cutting strips formed by bending a metal plate formed with alternating parallel slots and cutting strips. A plurality of spaced apart protruding cutting edges having a first acute cutting angle is formed along two opposite sides of the cutting strips. A plurality of recessed cutting edges having a second acute cutting angle is formed between the plurality of protruding cutting edges. The protruding cutting edges of one cutting strip are facing the recessed cutting edges of an adjacent cutting strip, thereby generating continuous hair-lifting and hair-cutting actions as the open cutter is driven in oscillating directions by a motor. A method for fabricating the open cutter is also disclosed.

5 Claims, 2 Drawing Sheets

